HydraBollard AE632

Automated Equipment Co.

Use anywhere you want to keep vehicles out without disrupting pedestrian traffic flow:

- ⇒ Stadiums
- ⇒ Parking Facilities
- ⇒ Alleyways
- ⇒ Boat Launch Control
- ⇒ Parks & Trails
- ⇒ Emergency Vehicle Access





- ♦ 6 5/8" diameter schedule 40 pipe
- Rises to 32" height
- Reflective finish
- **♦** Easy swap-out replacement
- Safe for pedestrians when open or closed



Automated Equipment Company 10847 E. Marginal Way S. Seattle, WA 98168 (206) 767-9080 FAX (206) 767-9077 1-800-338-7649 www.hydrabollard.com



Specifications

Single Bollard and Single Power Pack

MOTOR 1/2 HP

HYDRAULIC PACK 1.5 gpm & 300 psi

POWER SUPPLY 120V/220V

AMP DRAW 4-8 AMPS

CYLINDER SPEEDS Extend 12 seconds Retract 10

seconds (may vary with weather conditions)


CYLINDER DIMENSIONS 32" High x 6 5/8" Diameter

COLOR Caution Yellow w/ reflective

Striping

TEMPATURE RANGE -60°F to 240°F

DUTY CYCLE Continuous



Options

DUAL BOLLARDS W/ INDEPENDENT OPERATION
STAINLESS STEEL FABRICATION
COLOR (Caution Yellow is standard)
HEATERS FOR BOLLARD AND CONTROL CABINET
BATTERY BACKUP
220VAC or 208VAC
ACCESS CONTROL DEVICES



Snow country community access



Fabrication and installation



(206) 767-9080 FAX (206) 767-9077 1-800-338-7649 www.hydrabollard.com



Boat launch controlled access



Pay station and lane selection for boat launch

